

DAIRY TUBES

Our **Dairy Tubes** are available in ASTM A270 SS 304 and SS 316L.

Available in SMS and DIN Standard (6-meter length).

External and internal mechanically polished to at least 180 grit.



SMS and DIN Dairy Tubes

SMS	OD x Wall Thickness	DIN	OD x Wall Thickness
0.5"	12.7x1.65mm	DN10	13x1.5mm
0.75"	19.05x1.65mm	DN 15	19x1.5mm
-	-	DN 20	23x1.5mm
1"	25.4x(1.25 or 1.65mm)	DN 25	29x1.5mm
-	-	DN 32	35x1.5mm
1.5"	38.1x(1.25 or 1.65mm)	DN 40	41x1.5mm
2"	50.8x(1.25 or 1.65mm)	DN 50	53x1.5mm
2.5"	63.5x1.5mm	DN 65	70x2mm
3"	76.2x1.6mm	DN 80	85x2mm
4"	101.6x2mm	DN 100	104x2mm
-	-	DN 125	129x2mm
-	-	DN 150	154x2mm

How are Dairy Stainless-Steel Tubes different from other stainless-steel pipes?

At first glance, Sanitary Stainless-Steel Tubes look the same as other stainless-steel pipes, even the material composition looks similar. Here is how you can tell the difference.

- To qualify as sanitary, the internal surface has to be polished to at least 150 Grit, much smoother than non-sanitary tubes, but because of low price difference, markets today offer Sanitary Tubes with at least 180 Grit.
- The easiest way to identify Sanitary Tubes is the price. Because all Sanitary Tubes, Fittings and Valves in Malaysia have to be imported, the prices are usually higher than other stainless-steel products.